

Groves Incorporated

Manufacturers of Ready Rack and Groves Glass & Stone Storage Systems
818 Trakk Lane Woodstock, IL 60098 Phone: 800-991-2120 Fax: 815/338-8640
www.groves.com e-mail: sales@groves.com

ASSEMBLY INSTRUCTIONS FOR SINGLE SIDED SHOP CART (SSSC-7248)

When you receive your shipments, compare number of pieces received with your packing list.

1. Lay out base frame.
2. Attach casters using 3/8" x 1" hex cap screws, and 3/8" flange nuts. Be sure to install the two swivel and two rigid casters on the same end of the cart.
3. Install uprights with handle to base of cart using bolts, washers, lock washers, and nuts from package provided. Do not tighten bolts until cart is fully assembled.
4. Place upright on base lining up holes on base of upright to holes on base of cart. Feed bolt down thru the top of the flange on the upright and thru the base of the cart. Secure bolt at the bottom of cart with 1 washer, 1 lock washer, and 1 nut. Complete these steps for both side uprights.
5. Install the cross braces by lining up the hole in the brace to the holes on the inside of the upright with the rubber facing forward. (Note: the two top cross braces have strap loops located on the top.)
6. Use remaining bolts, washers, and nuts to secure the remaining cross braces with the rubber facing forward.
7. Once cart is fully assembled, go back and tighten down all bolts to make sure cart is secure.

Safety Note:

Weight capacity is 2,000 pounds.

Make sure load is evenly distributed and secured to the cart using ratchet straps.